

65" 75" 86"

GO+ 5

Technical Specification



4K Ultra HD Display



A73 x 4 CPU



Android 14.0



40 Touch Points



16W x 2 Speaker



2 x PEN SLOT
2 x 16W SPEAKER



Airclass Voting



Palm Swipe Erasing



Over The Air Updates



Wi-Fi 6



Bluetooth 5.2



QR Code Screen lock



10 Bit Color



Slim Frame



Zero Bonding Technology



Double Pen Function



Screen Recorder



Safe Operating System



Specific Software Solutions



Screen Share



info@emkotech.com



+90 212 886 86 85



emkotech.com

65" GO⁺ 5

Technical Specification

Display Parameters

LCD size	65"
Response Time	6.5ms
Aspect Ratio	16:9
Display Area	1428.48(H) x 803.52(V)mm
Pixel Pitch	0.372x0.372mm
Resolution	3840(H) x 2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
NTSC	72%
Contrast Ratio	5000:1
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness with glass(min)	400cd/m ²
Brightness with glass(typ)	450cd/m ²
Operation Time	7 daysx16 hours
Life Time	≥50000 Hours

Operating System

System version	Android 14
CPU	A73 x 4
GPU	Mali G52 MC1
RAM	4G
ROM	32G

Touch Specification

Sensing Type	Infrared recognition
Touch Tool	Passive infrared pen
Accuracy	±1.5mm
Touch Point	40 touch points
Minimum Object Size	3mm
Writing Height	≤2mm
Interpolation Resolution	32768(W)x32768(D)
Response Time	≤8ms
System	Windows 11/ Android Linux/Mac OS X/Chrome

Onboard Interface

HDMI IN	x 3
USB 2.0	x 1
USB 3.0	x 3
USB Type-C IN	x 1
TOUCH 2.0	x 2
AUDIO IN	x 1
AUDIO OUT	x 1
SPDIF	x 1
RS232	x 1
RJ45 IN	x 1

Audio

Sound Channel	2.0
Speaker Power	2 x 16W
Sound Pressure Level	84 dB

Bluetooth

Version	5.2
Working Frequency	2.4GHz
Working Distance	0~10m

Wi-Fi

Working Frequency	2.4GHz/5GHz
Working Distance	0~10m

Power

Power Requirements	100-240V~50/60Hz 3.5A
--------------------	-----------------------

Physical Specification

Dimension L x H x D	1491x898x99mm
Dimension(package) L x W x H	1628x185x1014mm
Thickness of Machine and wall mount	124mm(WIB6540B)
Wall-hanging Screw Spec	M8 x 25mm
VESA	600 x 400mm
Net Weight	32.05kg
Gross Weight	40.95kg

Accessories

Power cord	x 1
Writing pen	x 2
VESA Mount	x 1
HDMI Cable	x 1
Remote Control	x 1

Environmental Conditions

Operation temperature	0°C - 40°C
Operation humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Storage humidity	10% - 90%RH

75" GO⁺ 5

Technical Specification

Display Parameters

LCD size	75"
Response Time	6.5ms
Aspect Ratio	16:9
Display Area	1650.24(H)×928.26(V)mm
Pixel Pitch	0.42975×0.42975mm
Resolution	3840(H) x 2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
NTSC	72%
Contrast Ratio	5500:1
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness with glass(min)	400cd/m ²
Brightness with glass(typ)	450cd/m ²
Operation Time	7 days×16 hours
Life Time	≥50000 Hours

Operating System

System version	Android 14
CPU	A73 x 4
GPU	Mali G52 MC1
RAM	4G
ROM	32G

Touch Specification

Sensing Type	Infrared recognition
Touch Tool	Passive infrared pen
Accuracy	±1.5mm
Touch Point	40 touch points
Minimum Object Size	3mm
Writing Height	≤2mm
Interpolation Resolution	32768(W)×32768(D)
Response Time	≤8ms
System	Windows 11/ Android Linux/Mac OS X/Chrome

Onboard Interface

HDMI IN	x 3
USB 2.0	x 1
USB 3.0	x 3
USB Type-C IN	x 1
TOUCH 2.0	x 2
AUDIO IN	x 1
AUDIO OUT	x 1
SPDIF	x 1
RS232	x 1
RJ45 IN	x 1

Audio

Sound Channel	2.0
Speaker Power	2 x 16W
Sound Pressure Level	84 dB

Bluetooth

Version	5.2
Working Frequency	2.4GHz
Working Distance	0~10m

Wi-Fi

Working Frequency	2.4GHz/5GHz
Working Distance	0~10m

Power

Power Requirements	100-240V~50/60Hz 3.5A
--------------------	-----------------------

Physical Specification

Dimension L x H x D	1712×1022×99mm
Dimension(package) L x W x H	1863×225×1155mm
Thickness of Machine and wall mount	126mm(WIB9060H)
Wall-hanging Screw Spec	M8 x 25mm
VESA	800 x 400mm
Net Weight	42.15kg
Gross Weight	56.55kg

Accessories

Power cord	x 1
Writing pen	x 2
VESA Mount	x 1
HDMI Cable	x 1
Remote Control	x 1

Environmental Conditions

Operation temperature	0°C - 40°C
Operation humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Storage humidity	10% - 90%RH

86" GO⁺ 5

Technical Specification

Display Parameters

LCD size	86"
Response Time	6,5ms
Aspect Ratio	16:9
Display Area	1895.04(H)×1065.96(V) mm
Pixel Pitch	0.4935×0.4935 mm
Resolution	3840(H) x 2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
NTSC	72%
Contrast Ratio	5000:1
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness with glass(min)	400cd/m ²
Brightness with glass(typ)	450cd/m ²
Operation Time	7 days×16 hours
Life Time	≥50000 Hours

Operating System

System version	Android 14
CPU	A73 x 4
GPU	Mali G52 MC1
RAM	8GB
ROM	128GB

Touch Specification

Sensing Type	Infrared recognition
Touch Tool	Passive infrared pen
Accuracy	±1.5mm
Touch Point	40 touch points
Minimum Object Size	3mm
Writing Height	≤2mm
Interpolation Resolution	32768(W)×32768(D)
Response Time	≤8ms
System	Windows 11/ Android Linux/Mac OS X/Chrome

Onboard Interface

HDMI IN	x 3
USB 2.0	x 2
USB 3.0	x 3
USB Type-C IN	x 2
TOUCH 2.0	x 3
AUDIO IN	x 1
AUDIO OUT	x 1
SPDIF	x 1
RS232	x 1
HDMI OUT	x 1
DP IN	x 1
VGA IN	x 1
RJ45 OUT	x 1
RJ45 IN	x 1
TF CARD	x 1

Audio

Sound Channel	2.0
Speaker Power	2 x 16W
Sound Pressure Level	84 dB

Bluetooth

Version	5.2
Working Frequency	2.4GHz
Working Distance	0~10m

Wi-Fi

Working Frequency	2.4GHz/5GHz
Working Distance	0~10m

Power

Power Requirements	100-240V~50/60Hz 4.5A
--------------------	-----------------------

Physical Specification

Dimension L x H x D	1957×1159.9×97.4mm
Dimension(package) L x W x H	2110×225×1291mm
Thickness of Machine and wall mount	127.4mm(WIB9060H)
Wall-hanging Screw Spec	M8 x 25mm
VESA	800 x 600mm
Net Weight	53.55kg
Gross Weight	63.75kg

Accessories

Power cord	x 1
Writing pen	x 2
VESA Mount	x 1
HDMI Cable	x 1
Remote Control	x 1

Environmental Conditions

Operation temperature	0°C - 40°C
Operation humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Storage humidity	10% - 90%RH

