

TOUCH KIOSK

Technical Specification



10-Point
Multi-Touch
Screen



Full HD



Android



2 GB
RAM



32 GB
ROM



HDMI



Internal
Speaker



Intelligent
Scheduling



24/7
Broadcasting
Capability



Slim and
Stylish
Design



User Friendly
Interface



Multiple
Network
Options



Comprehensive
Media
Support



Technical Specification

PANEL		Yerleşik Arayüz	
LCD size	49"	TF	x 1
Active Display Area	1073.8 x 604mm	USB OTG	x 1
Resolution	1920 x 1080	USB 2.0	x 1
Contrast Ratio	1200:1 (typ.)	LAN	x 1
Brightness	380cd/m ² (typ.)	INPUT INTERFACE	
Frequency	60Hz	HDMI	x 1
Viewing Angles	178°(H)/178°(V)	STRUCTURE	
Life Time	50,000hrs(min.)	Boyut(G x Y x D)	665.8 x 1797 x 66mm
SYSTEM		LANGUAGE	
RAM	2 GB	OSD	Multilingual support
SSD	32 GB	ACCESSORIES	
POWER SUPPLY		Güç Kablosu	x 1
Voltage	100V~240V,50-60HZ	Kullanım Kılavuzu	x 1
Power consumption(max.)	≤120W		
Standby power consumption	0.5W		
ENVIRONMENT			
Working Temperature	0°C - 40°C		
Storage Temperature	-10°C~60°C		
Storage Humidity	10%~90%RH		
Working Humidity	20%~85%RH		
Max working time(hours/day)	7 day x 24 hours		

- The supported resolution is 1920x1080, which provides high-quality visuals.
- Built-in digital signage publishing system; support timer switch on/off; support USB upgrade.
- Support image, video, music, dynamic text, PPT, interactive APP or software, dynamic sheet, website, static text, APK, office files, etc.
- Support text, LOGO, date/time/week, weather and title. Support background picture and background color. Local USB play.
- Landscape or portrait display switchable, smooth transmission without black screen.
- Support WAN, LAN, VPN/Wi-Fi network publishing, cross-regional, trans-provincial, multi-network easy networking.
- Friendly user graphic interface for publishing program, easy to realize play time, order, rate, content and other functions management. Get the program display perfectly.



Çakmaklı Mahallesi, Hadımköy Yolu Caddesi
Emko Center D:75, 34500
Büyüçekmece/İstanbul/Türkiye