

# 43" 55" 65" 75" WM SERIES

Technical Specification



Android  
11.0



4K Ultra HD  
Display



10W x 2  
Speaker



4 GB  
RAM



32 GB  
ROM



HDMI



TYPE-C

## Ports

- 2 x HDMI IN  
(43" and 55")
- 3 x HDMI IN  
(65" and 75")
- 1 x HDMI OUT
- 1 x USB 2.0
- 1 x USB 3.0
- 1 x USB TYPE-C
- 1 x AUDIO OUT
- 1 x SPDIF
- 1 x RS232
- 1 x RJ45 IN
- 1 x RJ45 OUT  
(only 65" and 75")



## Control Buttons

- Volume +
- Volume -
- Down
- Up
- Input
- Menu
- Power



Anti Glare  
Screen



Slim Frame



Screen  
Share



DC  
Dimming



Specific  
Software  
Solutions



Bluetooth



Wi-Fi



10 Bit  
Color



Horizontal and  
Vertical Use



CMS



Built in  
Gravity Sensor



info@emkotech.com



+90 212 886 86 85



emkotech.com

# Technical Specification

## Display Parameters

LCD size	43"
Aspect Ratio	16:9
Display Area	941.184(H) x 529.416(V)mm
Pixel Pitch	0.2451 x 0.2451mm
Resolution	3840(H) x 2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
NTSC	72%
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness with glass(min)	400cd/m <sup>2</sup>
Brightness with glass(typ)	450cd/m <sup>2</sup>
Life Time	≥50000 Hours
Operation Time	7 day x 16 hours

## Operating System

System version	Android 11.0
CPU	A55 x 4
GPU	Mali G52MP2
RAM	4G
ROM	32G

## Audio

Sound Channel	2.0
Speaker Power	2 x 10W
Sound Pressure Level	81 dB
Peak Power	54W

## Onboard Interface

HDMI IN	x 2
HDMI OUT	x 1
USB 2.0	x 1
USB 3.0	x 1
USB TYPE-C	x 1
AUDIO OUT	x 1
SPDIF	x 1
RS232	x 1
RJ45 IN	x 1

## Physical Specification

Dimension L x H x D	964.6 x 552.5 x 71.4mm
Dimension(package) L x W x H	1056 x 156 x 672mm
Thickness of Machine and wall mount	95.4mm(WIB4722A)
Wall-hanging Screw Spec	M6 x 12mm
VESA	200 x 200mm
Net Weight	9.90kg
Gross Weight	13.85kg

## Accessories

Power cord	x 1
HDMI Cable	x 1
Remote Control	x 1
Vesa	x 1

## Environmental Conditions

Operation temperature	0°C - 40°C
Operation humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Storage humidity	10% - 90%RH
Altitude	<5000m

## Power

Power Requirements	100-240V~50/60Hz 2.5A
--------------------	-----------------------

# Technical Specification

## Display Parameters

LCD size	55"
Aspect Ratio	16:9
Display Area	1209.6(H) x 680.4(V)mm
Pixel Pitch	0.315×0.315mm
Resolution	3840(H) x 2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
NTSC	72%
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness with glass(min)	400cd/m <sup>2</sup>
Brightness with glass(typ)	450cd/m <sup>2</sup>
Life Time	≥50000 Hours
Operation Time	7 day x 16 hours

## Operating System

System version	Android 11.0
CPU	A55 x 4
GPU	Mali G52MP2
RAM	4G
ROM	32G

## Audio

Sound Channel	2.0
Speaker Power	2 x 10W
Sound Pressure Level	81 dB
Peak Power	54W

## Onboard Interface

HDMI IN	x 2
HDMI OUT	x 1
USB 2.0	x 1
USB 3.0	x 1
USB TYPE-C	x 1
AUDIO OUT	x 1
SPDIF	x 1
RS232	x 1
RJ45 IN	x 1

## Physical Specification

Dimension L x H x D	1233×703.5×71.4mm
Dimension(package) L x W x H	1332×156×819mm
Thickness of Machine and wall mount	95.4mm(WIB4722A)
Wall-hanging Screw Spec	M6 x 12mm
VESA	400 x 200mm
Net Weight	13.40kg
Gross Weight	19.50kg

## Accessories

Power cord	x 1
HDMI Cable	x 1
Remote Control	x 1
Vesa	x 1

## Environmental Conditions

Operation temperature	0°C - 40°C
Operation humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Storage humidity	10% - 90%RH
Altitude	<5000m

## Power

Power Requirements	100-240V~50/60Hz 3.0A
--------------------	-----------------------

# Technical Specification

## Display Parameters

LCD size	65"
Aspect Ratio	16:9
Display Area	1428.48(H)×803.52(V)mm
Pixel Pitch	0.372×0.372mm
Resolution	3840(H) x 2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
NTSC	72%
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness with glass(min)	400cd/m <sup>2</sup>
Brightness with glass(typ)	450cd/m <sup>2</sup>
Life Time	≥50000 Hours
Operation Time	7 day x 16 hours

## Operating System

System version	Android 11.0
CPU	A55 x 4
GPU	Mali G52MP2
RAM	4G
ROM	32G

## Audio

Sound Channel	2.0
Speaker Power	2 x 10W
Sound Pressure Level	80 dB
Peak Power	54W

## Onboard Interface

HDMI IN	x 3
HDMI OUT	x 1
USB 2.0	x 1
USB 3.0	x 1
USB TYPE-C	x 1
AUDIO OUT	x 1
SPDIF	x 1
RS232	x 1
RJ45 IN	x 1
RJ45 OUT	x 1

## Physical Specification

Dimension L x H x D	1463.3×838.3×76.4mm
Dimension(package) L x W x H	1628×208×942mm
Thickness of Machine and wall mount	101.4mm(WIB9080A)
Wall-hanging Screw Spec	M8×25mm
VESA	600×400mm
Net Weight	25.40kg
Gross Weight	33.25kg

## Accessories

Power cord	x 1
HDMI Cable	x 1
Remote Control	x 1
Vesa	x 1

## Environmental Conditions

Operation temperature	0°C - 40°C
Operation humidity	10% - 90%RH
Storage temperature	-20°C - 60°C
Storage humidity	10% - 90%RH
Altitude	<5000m

## Power

Power Requirements	100-240V~50/60Hz 3.5A
--------------------	-----------------------

# Technical Specification

Display Parameters		Physical Specification	
LCD size	75"	Dimension L x H x D	1685.6×963.7×81.6mm
Aspect Ratio	16:9	Dimension(package) L x W x H	1863×225×1090mm
Display Area	1649.664(H)×927.936(V)mm	Thickness of Machine and wall mount	101.4mm(WIB9080A)
Pixel Pitch	0.4296×0.4296mm	Wall-hanging Screw Spec	M8×25mm
Resolution	3840(H) x 2160(V)	VESA	800×600mm
Refreshing Frequency	60Hz	Net Weight	34.65kg
Display Color	1.07B(10bit)	Gross Weight	48.15kg
NTSC	72%		
Viewing Angle	178°(H/V)		
Back Light Unit	DLED		
Brightness with glass(min)	400cd/m <sup>2</sup>		
Brightness with glass(typ)	450cd/m <sup>2</sup>		
Life Time	≥50000 Hours		
Operation Time	7 day x 16 hours		
Operating System		Accessories	
System version	Android 11.0	Power cord	x 1
CPU	A55 x 4	HDMI Cable	x 1
GPU	Mali G52MP2	Remote Control	x 1
RAM	4G	Vesa	x 1
ROM	32G		
Audio		Environmental Conditions	
Sound Channel	2.0	Operation temperature	0°C - 40°C
Speaker Power	2 x 10W	Operation humidity	10% - 90%RH
Sound Pressure Level	80 dB	Storage temperature	-20°C - 60°C
Peak Power	54W	Storage humidity	10% - 90%RH
		Altitude	<5000m
Onboard Interface		Power	
HDMI IN	x 3	Power Requirements	100-240V~50/60Hz 4.5A
HDMI OUT	x 1		
USB 2.0	x 1		
USB 3.0	x 1		
USB TYPE-C	x 1		
AUDIO OUT	x 1		
SPDIF	x 1		
RS232	x 1		
RJ45 IN	x 1		
RJ45 OUT	x 1		

